SPECIFICATIONS FOR DOTY & SONS, INC. 30" SQUARE x 30" HIGH MUNDELEIN STYLE PLANTER (ITEM NO. MTP3030)

GENERAL DIMENSIONS:

Size: 30" Square Height: 30" Weight: 680 lbs. Minimum wall thickness: 3" 4" Square drain hole in center of bottom



Shown in Graphite finish

CONCRETE SPECIFICATIONS:

Sand: washed torpedo sand Stone: 3/8" washed pea gravel or 3/8" crushed limestone (if specified) Cement: very light gray color, 7-7 1/2 bags per cubic yard. Water Reducers used to increase strength and durability. Chemical Entrained Air: 6 to 8%, causes concrete to be more salt and chloride resistant. Average Strength (after 28 days) - 5000 psi minimum. Concrete cured indoors under plastic before exposure to outside air. Reinforcing: 3/8" reinforcing rebar used throughout sides and bottom. Rebar placed at least 1" away from outside surfaces.

SPECIAL FINISHES:

SB2 Sandblast Mesa Buff Color SB3 Sandblast Terra Cotta Color SB4 Sandblast Brown Color SB5 Sandblast Brick Red Color SB8 Sandblast Black Granite with Black Color SB9 Sandblast Beige Color SB10 Sandblast Sunset Rose Color C2 Light Sandblast Limestone Color French Grav Kahlua Graphite Other colors and finishes are available.

FINISHES:

Sandblast (SB). Standard finishes include:

SB1 Sandblast Tan Blend Pea Gravel, SB6 Light Sandblast Natural Gray Color SB7 Sandblast Light Gray Limestone.

OPTIONAL SEALER:

Acrylic sealer is not necessary, but we recommend it because it greatly enhances the beauty of the stone, resists salt, chloride, and makes graffiti clean-up easier. If ordered, Doty & Sons applies two coats at our factory.

> Doty & Sons Concrete Products, Inc. 1275 E. State St., Sycamore, IL 60178 Toll Free: 800-233-3907 Fax: 815-895-8035 Web Site: www.dotyconcrete.com