Doty & Sons Concrete Products, Inc. 12" Sq. Top tapers to 24" Sq. Bottom x 42" High ITEM - TB122442

Dimensions:

Size: 12" Sq. Top tapers to 24" Sq. at the bottom. Height: 42" Weight: 980 lbs.



TB122442 Bollard Shown in SB11 light sandblast finish

CONCRETE SPECIFICATIONS:

<u>Sand</u>: washed torpedo sand. <u>Stone</u>: 3/8" washed gravel. <u>Cement</u>: very light gray color, 7 to 7 1/2 bags per cubic yard. <u>Water reducers</u> used to increase strength & durability. <u>Chemically entrained air (6-8%)</u> causes concrete to be salt and chloride resistant. <u>Average strength (after 28 days) - 5000 PSI (compression strength varies depending on chosen finish)</u>. Concrete cured indoors under plastic cover before exposure to outside elements.

REINFORCING: Rebar cage held at least 1" away from outside surface.

All material used in this product meet ASTM standards.

FINISHES:

Available in sandblast (SB) finishes. Standard finishes: SB1, SB6 and SB7. Special finishes available. See color brochure or visit www.dotyconcrete.com for more information.

OPTIONAL SEALER:

Optional Two (2) coats of Acrylic Sealer is optional and is used to enhance and deepen the color of the finish and to provide protection against the elements. It resists salt & chloride, and makes graffiti cleanup easier. Your choice of Non-Gloss Sealer (ACR2) or Semi-Gloss Acrylic Sealer (ACR3). There is an additional charge for sealer. Call for more information.

B241242 Bollard Spec. Sheet Folder/Bollards Updated 9.12.19

Doty & Sons Concrete Products, Inc. 1275 E. State St., Sycamore, IL 60178 Toll Free: 800-233-3907 Fax: 815-895-8035 Web Site: www.dotyconcrete.com